

Specification Sheet for Vision Plus (39.75")

Axle Length	39.75"
Brace Height	7"
Limb Length	16"

*Note:- Brace heights may vary depending on cam size and type. It is more important to use the axle length as a point of reference, more than the brace height.

STRING AND CABLE CHARTS

	String	Power Cable	Control Cable	Split Cable (Long)	Split Cable (Short)
<i>Omega No.1</i>	62	41.25	43.25	-	-
<i>Omega No.2</i>	58	41.25	43.25	-	-
<i>Omega No.3</i>	55	41.25	43.25	-	-
<i>Rapid 2 No.R2</i>	58	41.25	-	64.5	9.5
<i>Rapid 2 No.R3</i>	55	41.25	-	64.5	9.5
<i>Rapid 2 No.R4</i>	51.5	41.25	-	64.5	9.5
<i>T-Wheel No.1</i>	58.25	41.25	-	64.5	9.5
<i>T-Wheel No.2</i>	55	41.25	-	64.5	9.5
<i>T-Wheel No.3</i>	53	41.25	-	64.5	9.5
<i>T-Wheel No.4</i>	49.5	41.75	-	64.5	10

MODULE SELECTION CHARTS

OMEGA CAM	OM1	OM2	OM3	OM4	OM5
<i>Cam No.1</i>	31.5	31	30.5	30	29.5
<i>Cam No.2</i>	29	28.5	28	27.5	27
	XM1	XM2	XM3	XM4	XM5
<i>Cam No.3</i>	26.5	26	25.5	25	24.5

RAPID 2 (Target Module)	RP1	RP2	RP3	RP4	RP5
<i>Cam No.R2</i>	30.5	30	29.5	29	28.5
<i>Cam No.R3</i>	28.5	28	27.5	27	26.5
<i>Cam No.R4</i>	26.5	26	25.5	25	24.5

RAPID 2 (Turbo Module)	TB1	TB2	TB3	TB4	TB5
<i>Cam No.R2</i>	30.5	30	29.5	29	28.5
<i>Cam No.R3</i>	28.5	28	27.5	27	26.5
<i>Cam No.R4</i>	26.5	26	25.5	25	24.5

T-WHEEL	HS1 65% SS1 65%	HS1 55% SS1 55%	HS2 65% SS2 65%	HS2 55% SS2 55%
<i>Cam No.1</i>	29		28	
<i>Cam No.2</i>	27		26	
<i>Cam No.3</i>	26		25	
<i>Cam No.4</i>	24		23	